

TBM VENTILATED WHEELS

The TBM ventilated wheels are available in the wide range of non-woven nylon fibre fabrics, in aluminium oxide or silicone carbide, and in various grains and dimensions.

They can be used on manual or automatic machines. They are particularly suitable to be assembled in order to make a long roller to be used on benchmounted or pillar machines.



APPLICATIONS

METAL

They are used for satin finishing of metal surfaces where there are space problems. Thanks to their ventilated construction, the ventilated and radial wheels allow a more uniform and homogeneous finishing.

STANDARD PRODUCTION FOR ALUMINIUM OXIDE

AVAILABLE GRADES	GRAIN	COLOUR
A—COARSE	80	Brown
A—MEDIUM	120	Brown
A—FINE	240	Brown
A—VERY FINE SOFT	320	Brown
A—VERY FINE STRONG	320	Brown

STANDARD PRODUCTION FOR SILICONE CARBIDE

AVAILABLE GRADES	GRAIN	COLOUR
S—MEDIUM	120	Dark Grey
S—FINE	240	Dark Grey
S—VERY FINE	320	Dark Grey
S—SUPER FINE	400	Dark Grey
S—ULTRA FINE	600	Dark Grey
S—ULTRA FINE SPECIAL	1000	Dark Grey
S—ULTRA FINE SPECIAL 2	1200	Dark Grey

STANDARD DIMENSIONS

OUTER Ø	INNER Ø
200	55
250	80
300	80 / 130
350	80 / 130 / 180
400	130 / 180
450	180 / 230
500	230

AVAILABLE WITH 2 OR 4 SHEETS